



## Apollo ASP-2

### High-Speed, 2-Reader Network Controller

### (2 Reader Ports, 8 Supervised Inputs, 4 Outputs)

The high-performance ASP-2 is an open-hardware architecture, clustering network controller that fully supports up to two doors. The ASP-2 is open for integration with software solutions via intuitive SDKs across multiple languages. The ASP-2 fully leverages the embedded Linux™ OS to offer groundbreaking features like 3<sup>rd</sup> party application support. Communications are encrypted end-to-end (Host to reader), the firmware is encrypted, and user certificates are supported.

## Notable Features

- ▶ **OPEN HARDWARE PLATFORM**
  - > SDK allows for hardware integration into any cloud or on-site Host software
- ▶ **EMBEDDED LINUX™ OS**
- ▶ **FULLY CONFIGURABLE HARDWARE INTERFACES**
  - > Onboard interfaces support 4 doors using TTL or RS485 (OSDP) readers, or up to 8 doors using OSDP readers with extra licenses
- ▶ **HOST-TO-READER ENCRYPTION**
  - > All serial and network communications can be encrypted
- ▶ **RAPID DOWNLOAD SPEEDS**
  - > Performance of up to 10K cards per second
- ▶ **BIOMETRIC TEMPLATES STORED ONBOARD**
- ▶ **READER PORTS SUPPORT BOTH WIEGAND & OSDP READERS**

## Competitive Edge

- ▶ **NETWORK CLUSTERING**
  - > Controller-to-controller communications for features like shared anti-passback and improved Host connection performance
- ▶ **OEM / 3<sup>rd</sup>-PARTY DEVELOPED & INSTALLED APPS**
  - > User-developed, user-deployed, and user-maintained applications that run on the controller in a safe, containerized environment
- ▶ **ASYNCHRONOUS COMMUNICATIONS**
  - > Events are sent to the host in real time, without polling
- ▶ **SCRIPTING & INTERNAL VARIABLES**
  - > Without modifying firmware, users can create custom logic to meet specific system function requirements
- ▶ **COST-EFFECTIVE EXPANSION**
  - > Connect up to 16 OSDP readers with reader expansion licenses while reducing hardware costs
- ▶ **INDUSTRIAL OPERATING TEMPERATURE (-40°C to +85°C)**
- ▶ **PoE+ OPTION**
  - > PoE+ coupled with the auxiliary output power port enables fully securing a door without needing a DC power supply

## Security

- ▶ OpenSSL
- ▶ TLSv1.3 with TLS Server/Peer certificate checking
- ▶ AES256-SHA256
- ▶ OSDP Secure Channel
- ▶ SSCPv2; Meets ANSSI encryption requirements
- ▶ FIPS 201-2
- ▶ CAC
- ▶ TWIC
- ▶ Firmware upgrades are signed and encrypted

## Access Control

- ▶ Anti-Passback
- ▶ Threat levels
- ▶ Use Limits
- ▶ N man rule
- ▶ Occupancy Management
- ▶ Visitors and Escorts
- ▶ Elevator Control (Up to 128 floors)
- ▶ Host-Controlled Access Request
- ▶ Duress Code
- ▶ Keypad with flexible pin lengths
- ▶ Supported reader types:
  - > OSDP
  - > Wiegand
  - > Clock & Data
  - > SSCPv2
  - > FIPS 201 PKI-based card and legacy types
  - > Biometric

## POWER

- ▶ Input Power (VIN):
  - > 12-24VDC; 350mA typical MAX current
  - > PoE+
- ▶ Auxiliary Output Power: VIN passthrough; 1A MAX current
- ▶ Reader Port output power:
  - > VIN passthrough with 500mA MAX per port
  - > 12VDC regulated with 500mA MAX per port or 600mA MAX combined
- ▶ USB 5VDC; 500mA MAX current
- ▶ Onboard power supervision with backup power
  - > Events and RTC maintained through power failure

## ONBOARD HARDWARE INTERFACES

- ▶ 2 Reader Ports supporting up to 2 TTL readers or up to 8 RS485 readers
  - > Open-collector Buzzer output
  - > Supports single-wire and two-wire reader LED control when using the Buzzer output for LED control
- ▶ 8 Supervised or Unsupervised Inputs
  - > Configurable supervision values (12 pre-defined)
  - > High-speed input scanning with filtering/noise suppression to eliminate false alarms
  - > High-precision analog ICs for stability in noisy environments
- ▶ 4 Form-C Relay Outputs
  - > 2A @ 30VDC MAX rating
- ▶ 2 Unsupervised Inputs for Cabinet Tamper & Power Failure
- ▶ 2 Network Ports
  - > 1 dedicated 10/100 Ethernet port
  - > 2<sup>nd</sup> Ethernet port possible with USB-to-Ethernet adapter
- ▶ 2 Downstream, RS485 Serial Com Ports
  - > Multidrop up to 32 IO and/or Reader Interfaces per port
  - > 9,600 to 115,200 baud
  - > 2-wire interface; half-duplex
  - > Each port can be configured for a different RS485 protocol
- ▶ Micro SD card
- ▶ Micro USB 2.0 with OTG support

## MEMORY CAPACITY

- ▶ Minimum Memory Specs: 512MB Flash & 256MB RAM
- ▶ Up to 250,000 cards
- ▶ Up to 128 readers with standard configuration
- ▶ Configurable 100K+ Event buffer
- ▶ 300 Access Levels per controller
- ▶ 50 Access Levels per cardholder
- ▶ 127 Magnetic stripe card formats
- ▶ 127 Wiegand card formats

## NETWORK AND HOST

- ▶ Onboard web server for board configuration
- ▶ Host-initiated or controller-initiated connections
- ▶ Up to 5 concurrent Host connections with authorized-host list
- ▶ IPv4 / IPv6 (Static or DHCP)
- ▶ SNMP

## REGULATORY COMPLIANCE

- ▶ UL 294, UL294B, UL1076, UL2610
- ▶ ULC / ORD C1076
- ▶ CE Compliant
  - > EN 61000-6
  - > EN 50130-4
- ▶ FCC Part 15 Class A
- ▶ RoHS / Pb (Lead) Free

## GENERAL INFORMATION

- ▶ Industrial operation and storage temperature (-40°C to +85°C)
- ▶ 5% to 95% humidity
- ▶ Dimensions: 8in (203.2mm) x 5.5in (139.7mm) x 0.88in (22.35mm)
- ▶ Weight: 0.6 pounds (272 grams)
- ▶ SKU:**431600-431603** ASP-2 with PoE option  
**431604-431607** ASP-2 without PoE option

## SYSTEM DIAGRAM

